

Seaming Tape SP Grade

Fabric/Polyethylene Film Laminate for Shorter Pile Carpets

INTRODUCTION

Sport-Fix Seaming Tape SP is a specially constructed tape for use with the recommended Sport-Fix adhesive in forming strong bonds when seam jointing artificial grass carpets used in the surfacing of sports areas.

The tape consists of a strong geo textile fabric on one side and this is laminated to a polyolefinic film to prevent the penetration of adhesive through to the under surface. Sport-Fix Seaming Tape SP is for use with shorter pile carpets, where it is important to minimise the height of the tape and adhesive at the seam joint.

FEATURES

- Impervious to moisture ingress from the base.
- Strong rot proof geo-textile bonding medium.
- Constructed to lay flat when rolled out.
- Sealed back to prevent adhesive penetrating to base.
- Minimum thickness to prevent show through at seams.
- Ideal for tennis courts and similar sports surfaces.

METHOD OF USE

IMPORTANT: Before embarking on any work involving Sport-Fix Seaming Tape SP the Health and Safety Data Sheet should be carefully studied by those carrying out the work.

APPLICATION

Sport-Fix Seaming Tape SP is designed for use with specific Sport-Fix polyurethane adhesives. It is constructed to form strong bonds, particularly to shorter pile artificial grass carpets when used with this adhesive. The correct amount of Envirostik adhesive is applied to the tape by notched applicator in a central band of approx. 25 cm, to the fabric side of the tape. The edges of the carpet are pressed into the wet adhesive. For more detailed instructions on the use of this product see the Data Sheet for the relevant Sport-Fix adhesive.

PRODUCT CHARACTERISTICS

Colour & Form:	White geo textile/film coated backing.	
Bonding Medium:	Non-woven polyester geo textile.	
Backing Medium:	Modified polyolefin plastic.	
Roll Sizes:	Length:	100 m
	Width:	30 cm.
	Thickness:	0.40 - 0.45 mm.
Weight:	145 g/m ² .	
Tensile Strength:	310 N/5 cm.	
Temperature Stability:	-25°C to +70°C.	
Storage:	0 to 30°C.	
Packaging:	Rolls individually film wrapped, and palletised for transport.	

This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.