



Seaming Tape LMP Super Eco

Fabric/Geo-textile

INTRODUCTION

EnviroStik Seaming Tape LMP Super Eco is a specially constructed tape for use with the recommended EnviroStik adhesive in forming strong bonds when seam jointing artificial grass carpets used in the landscaping of busy leisure areas.

The tape consists of a strong green/grey geo-textile.

EnviroStik Seaming Tape LMP Super Eco product is made using 90-100% recycled plastic, meeting both the Recycled Claim Standard (RCS) and the Global Recycled Standard (GRS).

FEATURES

- Used for the current wide range of artificial grass carpet seam joints.
- Impervious to moisture ingress from the base.
- Strong rot-proof geo-textile bonding medium.
- Lays flat to substrate when rolled out.
- Sealed back to prevent adhesive penetrating to base.

METHOD OF USE

Important: Before embarking on any work involving EnviroStik Seaming Tape LMP Super Eco the Health and Safety Data Sheet should be carefully studied by those carrying out the work.

APPLICATION

EnviroStik Seaming Tape LMP Super Eco is designed for use with the range of EnviroStik adhesives specially made for use on artificial grass installations. It is constructed to form strong bonds to the back of the current wide range of artificial grass carpets when used with these adhesives. The correct amount of EnviroStik adhesive is applied by notched applicator to the rougher fabric side of the tape and the edges of the carpet are pressed into the wet adhesive.

For more detailed instructions on the use of this product see the Data Sheet for EnviroStik Multi-Purpose Adhesive.

PRODUCT CHARACTERISTICS

Colour & Form:	Green/grey geo-textile.	
Bonding Medium:	Non-woven polyester geo-textile.	
Backing Medium:	Modified Polyolefin film.	
Roll Size:	Length:	100m & 300m
	Width:	300mm & 200mm
	Thickness:	0.65 to 0.68mm
Weight:	145g/m ² .	
Tensile Strength:	>600N/100mm.	
Temperature Stability:	-25°C to +70°C.	
Storage:	0°C to +30°C.	
Packaging:	Rolls individually film-wrapped, and palletised for transport.	

This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.